

# POEP4

## 4-Port PoE Switch (Unmanaged)



### FEATURES:

- Two-layer industrial PoE switch
- MAC auto study and aging, MAC address list capacity is 8K
- Support IEEE802.3af, IEEE802.3at standard
- Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- Industrial wide temperature design

# Specifications:

Model	POEP4
Ethernet Port	1*100/1000 Base-X 1*10/100/1000 Base-T 4*10/100 Base-T(PoE power supply)
PoE Power Consumption	Each power $\leq 30W$ , Total $\leq 60W$
PoE Protocol	IEEE802.3af, IEEE802.3at
Switching Capacity	6.8G
Packet Forwarding Rate	3.57Mpps
Packet Buffer Memory	1Mb
MAC Table Size	8K
Flow Control	Enable by default
Application Humidity	10%-90%
Power	DC48~57V
Lightning Protection	Common Mode 4KV Differential Mode 2KV
Working Temperature	-30°C ~ 65°C
Weight	480g
Dimension (WxDxH)	150mm x 100mm x 30mm
Accessories	
Model	
PFT3900	155M 850nm,2km,LC,Multi-mode
PFT3950	1.25G 850nm,500m,LC,Multi-mode
PFT3910	155M 1310/1550nm,20km,LC,Single-mode
PFT3920	155M 1550/1310nm,20km,LC,Single-mode
PFT3960	1.25G 1310/1550nm,20km,LC,Single-mode
PFT3970	1.25G 1550/1310nm,20km,LC,Single-mode