

POEHP4L

4-Port Fast Ethernet PoE Switch



FEATURES:

- Layer two commercial switch
- Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards
- MAC auto learning, aging, MAC address capacity is 2K
- Supports MDI/MDIX self-adaptation
- RJ45 port supports 10/100 Mbps self-adaptation
- Supports IEEE802.3af and IEEE803.3at power supply standards
- Adopts metal enclosure
- Supports Hi-PoE 60W
- Supports DC 48-57V power supply

Specifications:

Model	POEHP4L
Ethernet Port	2*10/100Mbps Uplink ports 4*10/100Mbps PoE ports
PoE Power Consumption	Port1≤60W, Port2-4≤30W, Total≤60W
PoE Protocol	IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE
Switching Capacity	1.8Gbps
Packet Forwarding Rate	890kpps
Packet Buffer Memory	768Kb
MAC Table Size	2K
Flow Control	Enable by default
Application Humidity	10%~90%
Power	DC48~57V power adapter
Lightning Protection	Common Mode 2KV Differential Mode 0.5KV
Working Temperature	-10°C ~+ 55°C
Weight	0.3kg
Dimension (WxDxH)	130mm x 85mm x 26mm