



NO COMPUTER CONFIGURATION  
EXTREMELY EASY DEPLOYMENT



SOLUTIONS

- Easy dip switch configuration
- Point to point and point to multipoint configuration
- Transmission range from 200ft to 1.86 miles



**CONTACT US NOW!**  
[sales@tdsecuritysystems.com](mailto:sales@tdsecuritysystems.com)

# WIRELESS SOLUTIONS



## ► TDP2P-X

- 176 x 96 x 28.5mm
- Speed ≤ 150Mbps
- Chipset Atheros AR 9341 600MHz
- Transmission DSSS
- Frequency 5.8MHz
- Antenna Gain 16DBi
- POE 24VDC / 12VDC
- Memory DDR 64MB
- Storage 8MB Flash
- IEEE802.11n, IEEE802.11g, IEEE802.11b, IEEE802.3u
- 10/100Mbps LAN\*2

Perfect for our solar solutions!



## ► TDP2PX-900

- 205 x 205 x 132.3mm
- Speed ≤ 900Mbps
- Chipset QCA9563+ QCA9882
- Frequency 4900~6100MHz
- Antenna Gain 16DBi
- POE 48V 0.5A
- Memory DDR2 128MB
- Storage 16MB Flash
- 10/100/1000Mbps LAN\*2

## ► TDP2PX-150

- 205 x 205 x 132.3mm
- Speed ≤ 150Mbps
- Chipset Atheros AR9344 600MHz
- Transmission DSSS
- Frequency 4900~6100MHz
- Antenna Gain 12DBi
- POE 48V 0.5A
- Memory DDR2 64MB
- Storage 8MB Flash
- 10/100Mbps LAN\*2

**CONTACT US NOW!**  
[sales@tdsecuritysystems.com](mailto:sales@tdsecuritysystems.com)